

Ürün verileri sayfası

Teknik Özellikler



Lisans, EcoStruxure Operatör Terminal Uzmanı, profesyonel, buildtime, grup, 3 istasyon, daimi, dijital

HMIEOTEBTP3P

Ana

Ürün serisi	EcoStruxure operatör terminali Uzmanı
Ürün Ya da Bileşen Tipi	Lisans
biçim	Dijital
lisansın tipi	Profesyonel Node locked license
Model	Derleme zamanı
yazılım versiyonu	V4.2
Operating system requirement	Windows 10 64 bit Windows 11 64 bit
sistem gereksinimleri	8 GB RAM 30 GB hard-drive space .NET Framework 4.7.2 or later
Kullanıcı Dili	İngilizce İtalyanca Çince İspanyolca Fransızca Almanca Portekizce Korece

Tamamlayıcı

License category	Perpetual
------------------	-----------

haberleşme port protokolü	FTPS
	HTTP
	IPsec
	websocket
	Couzet Automation millenium 3 FBD
	Emerson Industrial Automation Modbus SIO master
	Emerson Industrial Automation Modbus TCP master
	Emerson Process Management ROC Plus Ethernet
	Emerson Process Management ROC SIO
	Mitsubishi A series Ethernet
	Mitsubishi FX series computer link
	Mitsubishi FX series CPU direct
	Mitsubishi FX series Ethernet
	Mitsubishi iQ-R/F series Ethernet SLMP client
	Mitsubishi Q series CPU direct
	Mitsubishi Q series QnU CPU Ethernet
	Mitsubishi Q/QnA series serial
	Modbus Organization Modbus SIO ASCII master
	Modbus Organization Modbus SIO master
	Modbus Organization Modbus SIO slave
	Modbus Organization Modbus TCP master
	Modbus Organization Modbus TCP slave
	Omron CS/CJ/CP series host link
	Omron CS/CJ/CP/NX series Ethernet
	Omron CS/CJ/NJ/NX series Ethernet/IP
	OPC UA Foundation OPC UA server
	Rockwell Automation DF1
	Rockwell Automation DH485
	Rockwell Automation Ethernet/IP
	Schneider Electric Machine expert network
	Schneider Electric Modbus SIO master
	Schneider Electric Modbus TCP master
	Schneider Electric Modbus TCP master via USB
	Schneider Electric PacDrive
	Schneider Electric Uni-Telway
	Schneider Electric Zelio Logic
	Siemens Simatic S7 Ethernet
	Siemens Simatic S7 MPI direct
	Siemens TIA portal Ethernet
	CAN in Automation (CiA) CANopen slave
	PROFIBUS International Profibus DP slave

yazılım fonksiyonu	Alarms and events Barcode input Grafik ekran Blocky script Compound objects Color themes Convertors Data and operation logging Dockable windows interface environment Export with CSV and tab delimiter Expressions Gauges Icon libraries Image libraries Import export with CSV, tab and period delimiter Import with CSV and tab format IT communication Lamps Layouts Math functions Multi language development Multi language tables Object binding and properties OT communication Project transfer (Ethernet, filesystem, USB cable) Professional screen design Project and application settings Project libraries Recipes Screens (contents and folders) Security (levels, project, users) Simulation Symbols Tag import System keypad Switches Target binding and properties Text script Eğilim Variable (arrays, binding, properties, structures) Online and integrated help system OPC UA sunucusu Web server API Web viewer remote viewing and control
seri uyumluluğu	Harmony GTU Harmony GTUX Harmony ST6 Harmony STM6 Harmony STO7 Harmony iPC
Hosting option	On-premise
License size	Group (3 station)
Processor requirement	Intel core i3 8th generation Intel core i5 8th generation
ekran çözünürlüğü	320 x 240 pixels HVGA minimum 3840 x 2160 pixels 4K UHD maksimum

Environmental Data

Schneider Electric, ürün kullanım ömrünü ve geri dönüştürülebilirliği uzatmak amacıyla devam eden "Use Better, Use Longer, Use Again" kampanyamız aracılığıyla tedarik zinciri ortaklıkları, daha düşük etki malzemeleri ve döngü yoluyla 2050 yılına kadar Net Sıfır değerine ulaşmayı hedeflemektedir.

[Açıklanan Environmental Data >](#)

[Ürün sürdürülebilirliğini nasıl değerlendiriyoruz >](#)

Use Longer



Kullanım ömrü uzatma

Onarım

Hayır